P.O. Box 50325
Los Angeles, CA 90050
(323) 858-1261

MATERIAL SAFETY DATA SHEET

DATE PREPARED: 05/26/04 **DATE REVISED:**

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT IDENTITY: REMOVABLE MOVIE PROP SPRAY PAINT (ALL COLORS)

NFPA RATING: HEALTH 1, FLAMMABILITY 3, REACTIVITY 0

COMPANY: MOVIE PAINT, INC

TELEPHONE NUMBER:

2. COMPOSITION/INFORMATION ON INGREDIENTS

	CAS NUMBER	% BY WEIGHT	EXPOSURE LIMIT
ETHYL ALCOHOL	64-17-5	40 - 60	1000 ppm TWA
1, 1 DIFLUOROETHANE	75-37-6	25 - 50	1000 ppm TWA
ACETONE	67-64-1	5 - 10	1000 ppm TWA
ISOBUTANE	6847-86-8	5 - 10	800 ppm PEL

3. HAZARDS IDENTIFICATION - SINGLE OVEREXPOSURE - POTENTIAL HEALTH EFFECTS

EYE: CAN CAUSE EYE IRRITATION. SYMPTOMS INCLUDE STINGING, TEARING, REDNESS, SWELLING

SKIN: CAN CAUSE SKIN IRRITATION WITH FREQUENT USE. MAY AGGRAVATE EXISTING DERMATITIS CONDITION

SWALLOWING: SWALLOWING SMALL AMOUNTS OF MATERIAL DURING NORMAL USE IS NOT LIKELY TO CAUSE HARMFUL EFFECTS. ASPIRATION INTO THE RESPIRATORY SYSTEM DURING INGESTION OR VOMITING MAY CAUSE MILD TO SEVERE LUNG INJURY

INHALATION: BREATHING SMALL AMOUNTS OF THIS MATERIAL DURING NORMAL HANDLING IS NOT LIKELY TO CAUSE HARMFUL EFFECTS. INTENTIONAL INHALATION MISUSE BY SNIFFING OR CONCENTRATING THE VAPORS OF THIS PRODUCT OR INHALING LARGE AMOUNTS CAN CAUSE HEADACHES, DIZZINESS, ANESTHESIA, DROWSINESS, UNCONSCIOUSNESS AND OTHER CENTRAL NERVOUS SYSTEM EFFECTS INCLUDING DEATH

4. FIRST AID PROCEDURES

EYES: FLUSH EYES WITH LARGE AMOUNTS OF COOL WATER FOR AT LEAST 15 MINUTES OR UNTIL IRRITATION SUBSIDES. IF IRRITATION PERSISTS GET MEDICAL ATTENTION

SKIN: WASH EXPOSED AREA WITH SOAP AND WARM WATER. RINSE THOROUGHLY. GET MEDICAL ATTENTION IF IRRITATION OR REDNES PERSIST

SWALLOWING: DO NOT INDUCE VOMITING. GIVE PERSON A 8 OUNCE GLASS OF WATER TO DRINK AND CALL A POISON PREVENTION CENTER OR DOCTOR FOR HELP. DO NOT GIVE ANYTHING TO DRINK TO AN UNCONSCIOUS PERSON. DO NOT LEAVE AN UNCONSCIOUS PERSON UNATTENDED.

INHALATION: IF SYMPTOMS DEVELOP IMMEDIATELY MOVE PERSON TO FRESH AIR. IF SYMPTOMS PERSIST GET IMMEDIATE MEDICAL HELP. IF BREATHING IS DIFFICULT ADMINISTER OXYGEN. IN THE EVENT OF INTENTIONAL MISUSE GET IMMEDIATE MEDICAL HELP. IF NOT BREATHING ADMINISTER ARTIFICAL RESPIRATION AND GET IMMEDIATE MEDICAL HELP.

5. PHYSICAL PROPERTIES

AEROSOL PRODUCT. EXTREMELY FLAMMABLE. CONTENTS UNDER PRESSURE. DO NOT PUNCTURE OR INCINERATE CONTAINER. STORE BELOW 120° F KEEP FROM SOURCES OF FLAME, FIRE OR IGNITION. KEEP OUT OF REACH OF CHILDREN NOT INTENDED FOR USE AS A PERSONAL HAIR OR SKIN PRODUCT.

FLASH POINT - 150° F NFPA RATING: LEVEL 3, AEROSOL
EXPLOSIVE LIMITS: LEL 1 1, UEL 7 5%
AUTOIGNITION TEMPERATURE: NO DATA
REACTIVITY: STABLE. HAZARDOUS POLYMERIZATION WILL NOT OCCUR.
VAPOR DENSITY: HEAVIER THAN AIR.
VAPOR PRESSURE: 50 - 60 psig @ 70° F.
ODOR: FLORAL, ALCOHOL
APPEARANCE: FINE SPRAY
SOLUBILITY: SOLUBLE IN WATER
pH: N/A
EVAPORATION RATE (butyl acetate = 1): FASTER

Turnpeals.com

P.O. Box 50325
Los Angeles, CA 90050
(323) 858-1261

MATERIAL SAFETY DATA SHEET

DATE PREPARED: 5/26/04

PRODUCT IDENTITY: REMOVABLE MOVIE PROP SPRAY PAINT (ALL COLORS)

6. FIRE FIGHTING MEASURES

FIRE AND EXPLOSION HAZARDS: THIS MATERIAL IS VOLATILE AND RELEASES FLAMMABLE VAPORS BELOW AMBIENT TEMPERATURES AND READILY MIXES WITH AIR TO FORM FLAMMABLE MIXTURES WHEN EXPOSED TO AN IGNITION SOURCE ITS VAPORS ARE HEAVIER THAN AIR AND WILL TRAVEL LONG DISTANCES TO A POINT OF IGNITION. VAPORS WILL BURN IN THE OPEN OR EXPLODE IN CONFINED SPACES. THE LIQUID IS VOLATILE AND GIVES OFF INVISIBLE VAPORS. VAPOR OR LIQU MAY SETTLE INTO LOW AREAS. DECOMPOSITION PRODUCTS ARE HAZARDOUS. DECOMPOSITION BY HIGH TEMPERATURES (OPEN FLAME, GLOWING METAL SURFACES) FORM HYDROFLUORIC ACID AND POSSIBLE CARBONYL FLUORIDE.

EXTINGUISHING MEDIA: ALCOHOL FOAM, DRY CHEMICAL, CARBON DIOXIDE (CO_2). WATER SPRAYED ON HOT STORAGE CONTAINERS MAY RESULT IN BOILOVER.

FIRE FIGHTING INSTRUCTIONS: WEAR A SELF-CONTAINED BREATHING APPARATUS WITH FULL FACEPIECE OPERATED IN THE POSITIVE PRESSURE DEMAND MODE WITH APPROPRIATE TURN-OUT GEAR AND CHEMICAL RESISTANT PERSONAL PROTECTIVE EQUIPMENT.

ACCIDENTAL RELEASE MEASURES: SMALL SPILLS - ELIMINATE ALL SOURCES OF IGNITION SUCH AS FLAMES, PILOT LIGHTS, SPARKS, ELECTRICAL MOTORS, ETC. ABSORB LIQUID WITH VERMICULITE, OR OTHER ABSORBENTS SUCH AS CLAY KITTY LITTER OR FLOOR ABSORBENTS. PERSONS NOT WEARING PROPER PERSONAL PROTECTIVE CLOTHING SHOULD NOT BE ALLOWED IN THE AREA.

LARGE SPILLS: PREVENT RUN-OFF TO SEWERS, STREAMS OR OTHER BODIES OF WATER. IF RUN-OFF OCCURS NOTIFY PROPER AUTHORITIES THAT A SPILL HAS OCCURRED. TAKE SAME PRECAUTIONS AS ABOVE IN SMALL SPILLS.

7. HANDLING AND STORAGE:

AEROSOL PRODUCTS MUST BE STORED BELOW 120° F TO AVOID CONTAINER RUPTURING AND SPILLING OF CONTENTS. DO NOT PUNCTURE OR INCINERATE CONTAINERS. USE THIS PRODUCT IN ACCORDANCE WITH LABEL DIRECTIONS. OBSER\ LOCAL DEPARTMENT CODES AND REGULATIONS GOVERNING STORAGE.
SPECIAL PRECAUTION DO NOT SMOKE WHILE USING THIS PRODUCT. ALLOW SURFACES TO DRY THOROUGHLY PRIOR TO SMOKING. DO NOT SPRAY AROUND SOURCES OF IGNITION SUCH AS OPEN FLAMES, FIRE, HEATERS, HOT SURFACES, LIVE (ON) ELECTRICAL EQUIPMENT OR APPLIANCES. USE IN A WELL VENTILATED AREA.

8. PROTECTIVE EQUIPMENT:

WHEN HANDLED IN ACCORDANCE WITH LABEL DIRECTIONS AND THIS MSDS NO SPECIAL PROTECTIVE EQUIPMENT IS NECESSARY. OPTIONAL EQUIPMENT THAT MAY BE USED INCLUDES PROTECTIVE EYE WEAR AND APPROPRIATE BREATHING DEVICES.

9. DISPOSAL CONSIDERATIONS:

DO NOT DISPOSE OF PARTIALLY FULL OR FULL CONTAINERS. AEROSOL CONTAINERS ARE RE-CYCLABLE PROVIDING THEY ARE EMPTY OF THEIR CONTENTS. DO NOT PUNCTURE OR INCINERATE PARTIALLY FULL OR FULL CONTAINERS. OFFER EMPT CONTAINERS TO MUNICPAL WASTE DISPOSAL FACILITIES CAPABLE OF RE-CYCLING EMPTY AEROSOL CONTAINERS. IF IN DOUBT CONTACT LOCAL WASTE DISPOSAL AUTHORITY. DISPOSE OF CLEAN-UP WASTE IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS.

10. TRANSPORTATION INFORMATION:

US-DOT PROPER SHIPPING NAME: CONSUMER COMMODITY ORM-D

11. OTHER INFORMATION:

THE INFORMATION PRESENTED HEREIN IS BELIEVED TO BE ACCURATE BUT IS NOT WARRANTED TO BE WHETHER ORIGINATING WITH THE COMPANY OR NOT. RECIPIENTS ARE ADVISED TO CONFIRM IN ADVANCE OF NEED THAT THE INFORI ATION IS CURRENT AND APPLICABLE AND SUITABLE TO THEIR USES AND CIRCUMSTANCES.

THIS MSDS IS APPICABLE TO ALL COLOR VERSIONS OF **REMOVABLE MOVIE PROP SPRAY PAINT**. ALL COLOR VERSIONS MEE THE CURRENT CALIFORNIA AIR RESOURCES BOARD (CARB) REGULATIONS AS OF THIS MSDS DATE FOR FLAT PAINT SPRAY COATINGS. FOR ADDITIONAL INFORMATION CONTACT THE **MOVIE PAINT COMPANY, INC**.