

P-29 VINYL ELECTRICAL TAPE

APPLICATION

General-purpose, all-weather electrician's tape for **insulating wire splices and connections, harness wrapping, protecting conduits, and radio-television-appliance repair work.** Ideal for industrial maintenance applications and for wrapping tool handles.

FEATURES AND BENEFITS

- Provides required insulation with minimum bulk - its .007-inch-thick high voltage resistant vinyl backing is a space-saver.
- Underwriters' Laboratories listed. CSA certified.
- Non-corrosive adhesive.
- Flame retardant.
- Sunlight, oil, solvents and abrasion resistant.

TECHNICAL DATA

Backing material	Polyvinyl chloride (PVC) film
Adhesive	Rubber-based
Colors	Black
Total tape thickness	7.0 mils/0.178 mm
Tensile strength	20 lbs. per in./3.57 kg per cm
Elongation	200%
Unwind @ 150 FPM	50 oz. per in./558 gm per cm
Adhesion to steel	25 oz. per in./279 gm per cm
Dielectric strength	9,500 volts
Insulation resistance	1 x 10 ⁶ megohms (minimum)
Insulation Class	80° C
ASTM specification	D2301 Type 1
UL 510 Standard, 6/71	Flame retardant and sunlight resistant
Canadian Standards Association	C22.2
Gov't specification	HH-T-0025, MIL-I-7798A, HH-I-595C

Note: The above are typical values and should not be used in writing specifications.

STOCK SIZES

Refer to current price List.